



300PDL

**1060
Lpm**

**2.5
Bar**

**25m
Head**

**Diesel
Lombardini**

Diesel

300PDL

1060**Lpm****2.5****Bar**

Pairing the class leading Pacer S Pump with the Lombardini diesel engine gives an ideal combination to perform in any commercial or industrial application. The 2" pump is available with high flow or high pressure impeller with flows up to 871Lpm and pressures up to 4 Bar. The 3" pump offers flows up to 1060Lpm.



**Lombardini 15LD350R
Engine**

Pump

| | |
|---------------------------|----------------------------------|
| Make | Pacer |
| Model | S Series - SE3SL |
| Max Flow | 1060 Lpm |
| Max Pressure | 2.5 Bar |
| Body | Corrosion resistant polyester |
| Seals | EPDM (Buna & Viton available) |
| Mechanical seal | Carbon ceramic |
| Impeller | Polyester 975 - 4 vane |
| Inlet & Outlet | 3" NPT female |
| Suction lift | Up to 7.6m |
| Notes | Self priming after initial prime |

Engine

| | |
|----------------------|------------------------------|
| Make | Lombardini |
| Model | 15LD350R |
| Power | 7.5Hp - Gross / 5.1Hp - Net* |
| Shaft | 3/4" parallel keyway shaft |
| Fuel capacity | 4.3 Litres |
| Lubrication | Oil splash |
| Cooling | Air cooled |
| Fuel system | Direct injection |
| Starting | Recoil |

Weight & Dimensions

| | |
|-------------------|-----------------------|
| Weight | 41 Kg |
| Dimensions | L599 - W374 - H445 mm |

*Net power @ 3600 Rpm in accordance with DIN ISO 1585

WHISPER PUMPS LTD

Leen Court, Boughton, Newark, Nottinghamshire, NG22 9ZD

Registered in England No 4548322