



207PDL

757
Lpm

4
Bar

40m
Head

Diesel
Lombardini

Diesel

207PDL

757

4

Lpm

Bar



Pairing the class leading Pacer S Pump with the Lombardini diesel engine gives an ideal combination to perform in any commercial or industrial application. The 2" pump is available with high flow or high pressure impeller with flows up to 871Lpm and pressures up to 4 Bar. The 3" pump offers flows up to 1060Lpm.



Lombardini 15LD350R Engine

Pump

Make	Pacer
Model	S Series - SE2UL
Max Flow	757 Lpm
Max Pressure	4 Bar
Body	Corrosion resistant polyester
Seals	EPDM (Buna & Viton available)
Mechanical seal	Carbon ceramic
Impeller	Polyester 706 - 5 vane
Inlet & Outlet	2" NPT female
Suction lift	Up to 7.6m
Notes	Self priming after initial prime

Engine

Make	Lombardini
Model	15LD350R
Power	7.5Hp - Gross / 5.1Hp - Net*
Shaft	3/4" parallel keyway shaft
Fuel capacity	4.3 Litres
Lubrication	Oil splash
Cooling	Air cooled
Fuel system	Direct injection
Starting	Recoil

Weight & Dimensions

Weight	37.2 Kg
Dimensions	L529 - W374 - H445 mm

*Net power @ 3600 Rpm in accordance with DIN ISO 1585

WHISPER PUMPS LTD

Leen Court, Boughton, Newark, Nottinghamshire, NG22 9ZD

Registered in England No 4548322