



Whole House Water Boosting Systems

- Increased Water Pressure & Flow
- 125L - 1000L Tank Sizes
- Fixed or Variable Speed Controls
- Twin and Plus Pump Options

Compact, Slimline, Utility, Snug, Rectangular & Coffin Ranges

The Powertank range is a self-contained cold water booster set specifically designed for use in domestic, commercial, agricultural & industrial applications, where existing water pressure and flow is insufficient to meet demand. The range caters for multiple space and storage capacity requirements.

To increase water flow there must first be more water. If your mains supply is not meeting your requirements, then you need a break tank to store your own water supply ready for when you need it. This can then be pumped to your outlets on demand giving you a plentiful supply of water at the right pressure.

COMPACT



Compact: 125L

MODEL	STOCK CODE	PRICE	POWER		PERFORMANCE		HEIGHT	LENGTH	WIDTH
			P ₂		Q	H			
		£	kW	HP	L/min	m	mm	mm	mm
Single-Phase									
125L Compact Fixed Speed	2600070	961.00	0.55	0.75	35	30	850	560	490
125L Compact Variable Speed	2600080	1595.00	0.55	0.75	65	30	870	560	490

The Powertank Compact has been designed for smaller properties with low water pressure and flow and where space is at a premium. Fluid Category 5 - AB Air gap as standard.

SLIMLINE



Slimline: 200L, 350L & 450L

MODEL	STOCK CODE	PRICE	POWER		PERFORMANCE		HEIGHT	LENGTH	WIDTH
			P ₂		Q	H			
		£	kW	HP	L/min	m	mm	mm	mm
Single-Phase									
200L Slimline Fixed Speed	2600090	876.00	0.55	0.75	35	30	1190	N/A	584
200L Slimline Variable Speed	2600100	1497.00	0.75	1	80	30	1210	N/A	584
350L Slimline Fixed Speed	2600110	913.00	0.55	0.75	35	30	1656	N/A	584
350L Slimline Variable Speed	2600120	1533.00	0.75	1	80	30	1676	N/A	584
450L Slimline Fixed Speed	2601220	963.00	0.55	0.75	35	30	2100	N/A	584
450L Slimline Variable Speed	2601230	1583.00	0.75	1	80	30	2120	N/A	584

The Powertank Slimline will fit through a standard doorway and is suitable where floor space is limited. AF Air gap for Fluid Category 4 as standard (AB Air gap for Fluid Category 5 optional)

UTILITY



Utility: 500L & 750L

MODEL	STOCK CODE	PRICE	POWER		PERFORMANCE		HEIGHT	LENGTH	WIDTH
Single-Phase		£	P ₂	Q	H				
			kW	HP	L/min				
500L Utility Fixed Speed	2600130	931.00	0.55	0.75	35	30	1393	N/A	760
500L Utility Variable Speed	2600140	1551.00	0.75	1	80	30	1413	N/A	760
500L Utility Variable Speed PLUS	2600150	1886.00	1.5	2	140	30	1413	N/A	760
500L Utility Variable Speed TWIN	2600160	2985.00	1.5	2	160	30	1413	N/A	760
750L Utility Fixed Speed	2600170	1138.00	0.55	0.75	35	30	2113	N/A	760
750L Utility Variable Speed	2600180	1759.00	0.75	1	80	30	2133	N/A	760
750L Utility Variable Speed PLUS	2600190	2094.00	1.5	2	140	30	2133	N/A	760
750L Utility Variable Speed TWIN	2600200	3192.00	1.5	2	160	30	2133	N/A	760

AF Air gap for Fluid Category 4 as standard (AB Air gap for Fluid Category 5 optional)

* **PLUS** Systems feature a more powerful pump * **TWIN** Systems contain two pumps.

UTILITY



Utility: 650L & 1000L

MODEL	STOCK CODE	PRICE	POWER		PERFORMANCE		HEIGHT	LENGTH	WIDTH
Single-Phase		£	kW	HP	Q	H	mm	mm	mm
					L/min	m			
650L Utility Fixed Speed	2600210	1261.00	0.55	0.75	35	30	1283	1083	669
650L Utility Variable Speed	2600220	1881.00	0.75	1	80	30	1303	1083	669
1000L Utility Fixed Speed	2600230	1445.00	0.55	0.75	35	30	1640	1688	563
1000L Utility Variable Speed	2600240	2144.00	0.75	1	80	30	1660	1688	563
1000L Utility Variable Speed PLUS	2600250	2479.00	1.5	2	140	30	1660	1688	563
1000L Utility Variable Speed TWIN	2600260	3578.00	1.5	2	160	30	1660	1688	563

The Powertank Utility range is designed for domestic and light commercial use where there is low mains pressure and where pressure fluctuates. The Utility range is designed for areas where floor space is not restricted.

AF Air gap for Fluid Category 4 as standard (AB Air gap for Fluid Category 5 optional)

* **PLUS** Systems feature a more powerful pump * **TWIN** Systems contain two pumps.

SNUG



Snug: 350L

MODEL	STOCK CODE	PRICE	POWER		PERFORMANCE	HEIGHT	LENGTH	WIDTH	
Single-Phase		£	P ₂		Q	H			
			kW	HP	L/min	m			
350L Snug Fixed Speed	2603280	1171.00	0.55	0.75	35	30	700	1200	590
350L Snug Variable Speed	2603290	1756.00	0.75	1	80	30	700	1200	590
350L Snug Variable Speed TWIN	2603300	3110.00	1.5	2	160	30	700	1200	590

Specifically designed for under stairs installation.

RECTANGULAR



CAT4

Rectangular: 300L & 500L

MODEL	STOCK CODE	PRICE	POWER		PERFORMANCE		HEIGHT	LENGTH	WIDTH
Single-Phase		£	P ₂		Q		H	mm	mm
			kW	HP	L/min	m	mm		
300L Rectangular Fixed Speed	2600310	949.00	0.55	0.75	35	30	940	1045	665
300L Rectangular Variable Speed	2600320	1570.00	0.75	1	80	30	960	1045	665
500L Rectangular Fixed Speed	2600330	981.00	0.55	0.75	35	30	1030	1190	727
500L Rectangular Variable Speed	2600340	1601.00	0.75	1	80	30	1050	1190	727
500L Rectangular Variable Speed TWIN	2600350	3035.00	1.5	2	160	30	1050	1190	727

The Powertank Rectangular range is designed for areas where height restrictions and access are an issue.
AF Air gap for Fluid Category 4 as standard (AB Air gap for Fluid Category 5 optional)

* **TWIN** Systems contain two pumps.

COFFIN



CAT4

Coffin: 200, 270L & 450L

MODEL	STOCK CODE	PRICE	POWER		PERFORMANCE		HEIGHT	LENGTH	WIDTH
Single-Phase		£	P ₂		Q		H	mm	mm
			kW	HP	L/min	m	mm		
200L Coffin Fixed Speed	2600360	926.00	0.55	0.75	35	30	770	1106	475
200L Coffin Variable Speed	2600370	1770.00	0.75	1	80	30	790	1106	475
270L Coffin Fixed Speed	2600380	1128.00	0.55	0.75	35	30	751	1571	475
270L Coffin Variable Speed	2600390	1972.00	0.75	1	80	30	770	1571	475
340L Coffin Fixed Speed	2600400	1155.00	0.55	0.75	35	30	980	1571	475
340L Coffin Variable Speed	2600410	1985.00	0.75	1	80	30	1000	1571	475
450L Coffin Fixed Speed	2600420	1168.00	0.55	0.75	35	30	846	1765	580
450L Coffin Variable Speed	2600430	1992.00	0.75	1	80	30	866	1765	580

The Powertank Coffin range is designed for areas where height restrictions and access are an issue.
AF Air gap as standard.

CAT5



CAT5

CAT5 10L & 38L

MODEL	STOCK CODE	PRICE	POWER		PERFORMANCE		HEIGHT	LENGTH	WIDTH
Single-Phase		£	P ₂		Q		H	mm	mm
			kW	HP	L/min	m	mm		
10L CAT5 Fixed Speed	2600440	959.00	0.37	0.5	60	30	670	500	300
38L CAT5 Fixed Speed	2603260	1035.00	0.37	0.5	60	30	920	500	300

The Powertank CAT 5 provides backflow protection for fluid category 5 risks. Our system includes a type AB air-gap and has a water volume of either 10 or 38ltrs.